

URTK/S - Test disconnect terminal block



0311087

<https://www.phoenixcontact.com/au/products/0311087>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Test disconnect terminal block, with two test sockets for 4 mm test plugs, or for receiving bridge bars or screw bridges, nom. voltage: 400 V, nominal current: 41 A, connection method: Screw connection, 1 level, Rated cross section: 6 mm², cross section: 0.5 mm² - 10 mm², mounting type: NS 35/7,5, NS 35/15, NS 32, color: gray

Your advantages

- Easy and clear testing in current transformer secondary circuits can be performed using the test disconnect terminal blocks of the URTK/S range
- On both sides of the disconnect point, the terminal block has a test socket which can also be used to switch across to neighboring terminal blocks

Commercial Data

Item number	0311087
Packing unit	50 pc
Minimum order quantity	50 pc
Sales Key	BE1233
Product Key	BE1233
Catalog Page	Page 519 (C-1-2019)
GTIN	4017918001292
Weight per Piece (including packing)	35.51 g
Weight per Piece (excluding packing)	35.51 g
Customs tariff number	85369010
Country of origin	CN

Technical Data

Product properties

Product type	Test disconnect terminal block
Number of connections	2
Number of rows	1
Potentials	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	6 kV
Maximum power dissipation for nominal condition	1.31 W

Connection data

Number of connections per level	2
Nominal cross section	6 mm ²

1 level

Screw thread	M4
Tightening torque	1.2 ... 1.5 Nm
Stripping length	13 mm
Internal cylindrical gage	A5
Connection in acc. with standard	IEC 60947-7-1
Conductor cross section rigid	0.5 mm ² ... 10 mm ²
Cross section AWG	20 ... 8 (converted acc. to IEC)
Conductor cross section flexible	0.5 mm ² ... 6 mm ²
Conductor cross section, flexible [AWG]	20 ... 10 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve)	0.5 mm ² ... 6 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.5 mm ² ... 4 mm ²
2 conductors with same cross section, solid	0.5 mm ² ... 2.5 mm ²
2 conductors with same cross section, flexible	0.5 mm ² ... 6 mm ²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	0.5 mm ² ... 4 mm ²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve	0.5 mm ² ... 4 mm ²
Nominal current	41 A
Maximum load current	57 A (with 10 mm ² conductor cross section)
Nominal voltage	400 V
Nominal cross section	6 mm ²

Dimensions

Width	8.2 mm
-------	--------

URTK/S - Test disconnect terminal block



0311087

<https://www.phoenixcontact.com/au/products/0311087>

End cover width	2.2 mm
Height	72 mm
Height NS 35/15	59 mm
Height NS 35/7,5	51.5 mm
Height	2.028 "
Height NS 32	56.5 mm
Length	72 mm

Material specifications

Color	gray
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	27,5 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Electrical tests

Surge voltage test

Test voltage setpoint	7.3 kV
Result	Test passed

Temperature-rise test

Requirement temperature-rise test	Increase in temperature \leq 45 K
Result	Test passed
Short-time withstand current 6 mm ²	0.72 kA
Short-time withstand current 10 mm ²	1.2 kA
Result	Test passed

Power-frequency withstand voltage

Test voltage setpoint	1.89 kV
Result	Test passed

Mechanical properties

Mechanical data

URTK/S - Test disconnect terminal block



0311087

<https://www.phoenixcontact.com/au/products/0311087>

Open side panel	Yes
-----------------	-----

Mechanical tests

Mechanical strength

Result	Test passed
--------	-------------

Attachment on the carrier

DIN rail/fixing support	NS 32/NS 35
Test force setpoint	5 N
Result	Test passed

Test for conductor damage and slackening

Rotation speed	10 rpm
Revolutions	135
Conductor cross section/weight	0.5 mm ² / 0.3 kg
	6 mm ² / 1.4 kg
	10 mm ² / 2 kg
Result	Test passed

Environmental and real-life conditions

Needle-flame test

Time of exposure	30 s
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

Mounting

Mounting type	NS 35/7,5
	NS 35/15
	NS 32
Screw thread	M3

URTK/S - Test disconnect terminal block




0311087

<https://www.phoenixcontact.com/au/products/0311087>

Drawings

Circuit diagram




URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>



Schematic diagram




Three-phase transducer test set

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>

Schematic diagram



Simple current transformer test circuit

a = normal operation

b = measured value testing

c = transformer short-circuit

d = relay testing


URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>



Schematic diagram



Three-phase linked transducer test set

URTK/S - Test disconnect terminal block



0311087

<https://www.phoenixcontact.com/au/products/0311087>

Circuit diagram



URTK/S - Test disconnect terminal block



0311087

<https://www.phoenixcontact.com/au/products/0311087>


Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/au/products/0311087>

 CSA Approval ID: 13631				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	300 V	40 A	26 - 10	-

 IECEE CB Scheme Approval ID: NL-65058				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	400 V	-	-	- 6

 EAC Approval ID: RU C-DE.BL08.B.00534				
--	--	--	--	--

 cULus Recognized Approval ID: E60425				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
Use group B	300 V	50 A	26 - 8	-
Use group C	300 V	50 A	26 - 8	-

 KEMA-KEUR Approval ID: 71-113436				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	400 V	-	-	- 6

 LR Approval ID: LR2041789TA-02				
--	--	--	--	--

 RS Approval ID: 22.44.01.00083.250				
--	--	--	--	--

URTK/S - Test disconnect terminal block



0311087

<https://www.phoenixcontact.com/au/products/0311087>

Classifications

ECLASS

ECLASS-11.0	27141126
ECLASS-12.0	27141126
ECLASS-13.0	27250109

ETIM

ETIM 8.0	EC000902
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

URTK/S - Test disconnect terminal block



0311087

<https://www.phoenixcontact.com/au/products/0311087>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>

Accessories

 Note: Applying some accessories below might limit this product.


FB 10- RTK/S - Screw bridge

0311171

<https://www.phoenixcontact.com/au/products/0311171>



Screw bridge, pitch: 8.2 mm, number of positions: 10, color: silver

 Max. current carrying capacity: 41 A

EB 2- 8 - Insertion bridge

0202154

<https://www.phoenixcontact.com/au/products/0202154>



Insertion bridge, pitch: 8 mm, number of positions: 2, color: gray

 Max. current carrying capacity: 41 A

URTK/S - Test disconnect terminal block


0311087

<https://www.phoenixcontact.com/au/products/0311087>

EB 3- 8 - Insertion bridge

0202141

<https://www.phoenixcontact.com/au/products/0202141>




Insertion bridge, pitch: 8 mm, number of positions: 3, color: gray

 Max. current carrying capacity: 41 A

EB 10- 8 - Insertion bridge

0202138

<https://www.phoenixcontact.com/au/products/0202138>



Insertion bridge, pitch: 8 mm, number of positions: 10, color: gray

 Max. current carrying capacity: 41 A

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>

S - Switching lock

0308359

<https://www.phoenixcontact.com/au/products/0308359>



Switching lock, for disconnect slides, length: 12 mm, width: 8.2 mm, color: white


ASB 2-RTK/S - Switching jumper

0311281

<https://www.phoenixcontact.com/au/products/0311281>



Switching jumper, pitch: 8.2 mm, number of positions: 2, color: silver

 Max. current carrying capacity: 35 A

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>

USB 2-RTK/S - Switching jumper

0311278

<https://www.phoenixcontact.com/au/products/0311278>



Switching jumper, pitch: 8.2 mm, number of positions: 2, color: silver

 Max. current carrying capacity: 35 A

SB 4-RTK/S - Switching jumper

0311265

<https://www.phoenixcontact.com/au/products/0311265>



Switching jumper, pitch: 8.2 mm, number of positions: 4, color: silver

 Max. current carrying capacity: 35 A

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>


SB 2-RTK/S - Switching jumper

0311236

<https://www.phoenixcontact.com/au/products/0311236>



Switching jumper, pitch: 8.2 mm, number of positions: 2, color: silver

 Max. current carrying capacity: 35 A

EB 4- 8 - Insertion bridge

0202142

<https://www.phoenixcontact.com/au/products/0202142>



Insertion bridge, pitch: 8 mm, number of positions: 4, color: gray

 Max. current carrying capacity: 41 A

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>


EB 1/3/5/7-8 - Insertion bridge

3072340

<https://www.phoenixcontact.com/au/products/3072340>




Insertion bridge, pitch: 16.4 mm, number of positions: 4, pin assignment: 1, 3, 5, 7, length: 24 mm, color: gray

 Max. current carrying capacity: 41 A


EB 1/3/5-8 - Insertion bridge

3072341

<https://www.phoenixcontact.com/au/products/3072341>



Insertion bridge, pitch: 16.4 mm, number of positions: 3, pin assignment: 1,3,5, length: 24 mm, color: gray

 Max. current carrying capacity: 41 A

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>

D-URTK - Cover

0310020

<https://www.phoenixcontact.com/au/products/0310020>

Cover, length: 72 mm, width: 2.2 mm, height: 41.5 mm, color: gray



TS-RTK - Partition plate

0310211

<https://www.phoenixcontact.com/au/products/0310211>

Partition plate, length: 72 mm, width: 0.8 mm, color: gray



URTK/S - Test disconnect terminal block



0311087

<https://www.phoenixcontact.com/au/products/0311087>

ATS-RTK - Partition plate

0310224

<https://www.phoenixcontact.com/au/products/0310224>

Partition plate, length: 97.5 mm, width: 0.8 mm, height: 45.8 mm, color: gray



SBS 8:UNBEDRUCKT - Marker card

1007235

<https://www.phoenixcontact.com/au/products/1007235>

Marker card, Card, white, unlabeled, can be labeled with: Marker pen, mounting type: snap into tall marker groove, snap into flat marker groove, for terminal block width: 8 mm, lettering field size: 6 x 8.1 mm



URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>

SZS 1,0X4,0 VDE - Screwdriver

1205066

<https://www.phoenixcontact.com/au/products/1205066>



Screwdriver, slot-headed, VDE insulated, size: 1.0 x 4.0 x 100 mm, 2-component grip, with non-slip grip

AP-ME

METER - Cover profile

3034361

<https://www.phoenixcontact.com/au/products/3034361>



Cover profile, for covering terminal strips, snapped onto APT-ME cover profile carrier or APH-ME end bracket. A cover profile carrier should be positioned at the ends and at intervals of around 40 cm. Length supplied: 1 m

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>

APH-ME - Cover profile carrier

3034374

<https://www.phoenixcontact.com/au/products/3034374>

Cover profile carrier, for mounting on NS 35/7,5 DIN rail, for fixing the AP-ME cover profile, can be sealed as an option



APT-ME - Cover profile carrier

3034358

<https://www.phoenixcontact.com/au/products/3034358>

Cover profile carrier for mounting on NS 35/7.5 DIN rail for attaching the cover profile AP-ME



URTK/S - Test disconnect terminal block




0311087

<https://www.phoenixcontact.com/au/products/0311087>

TS-UK 6-T - Separating plate

3072820

<https://www.phoenixcontact.com/au/products/3072820>



Separating plate, length: 66.5 mm, width: 1 mm, height: 62.5 mm, color: gray

KSS 8 - Short-circuit connector

0311540

<https://www.phoenixcontact.com/au/products/0311540>



Short-circuit connector, pitch: 8 mm, number of positions: 2, color: black

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>

KSS 4- 8 - Short-circuit connector

0309549

<https://www.phoenixcontact.com/au/products/0309549>



Short-circuit connector, pitch: 8 mm, number of positions: 4, color: black

SCP 2-8 - Short-circuit connector

3070402

<https://www.phoenixcontact.com/au/products/3070402>



Short-circuit connector, pitch: 8.15 mm, number of positions: 2, color: orange

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>

SCP 3-8 - Short-circuit connector

3070403

<https://www.phoenixcontact.com/au/products/3070403>



Short-circuit connector, pitch: 8.15 mm, number of positions: 3, color: orange

SCP 4-8 - Short-circuit connector

3070404

<https://www.phoenixcontact.com/au/products/3070404>



Short-circuit connector, pitch: 8.15 mm, number of positions: 4, color: orange

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>

SCPI 2-8 - Short-circuit connector

3070423

<https://www.phoenixcontact.com/au/products/3070423>



Short-circuit connector, pitch: 8.15 mm, number of positions: 2, color: orange

SCPI 4-8 - Short-circuit connector

3070424

<https://www.phoenixcontact.com/au/products/3070424>



Short-circuit connector, pitch: 8.15 mm, number of positions: 4, color: orange

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>



NS 32 PERF 2000MM-VPE 10 - DIN rail perforated

1201002

<https://www.phoenixcontact.com/au/products/1201002>



DIN rail perforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver, Pack of 10 (20 m)

NS 32 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201015

<https://www.phoenixcontact.com/au/products/1201015>



DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, G profile, color: silver, Pack of 10 (20 m)

URTK/S - Test disconnect terminal block



0311087

<https://www.phoenixcontact.com/au/products/0311087>

NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/au/products/0801733>



DIN rail perforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/au/products/0801681>



DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>

NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/au/products/1204119>



DIN rail perforated, acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver, Pack of 25 (50 m)

NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/au/products/1204122>



DIN rail, unperforated, acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver, Pack of 10 (20 m)

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>



NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/au/products/0801704>



DIN rail, unperforated, acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver, Pack of 25 (50 m)

NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/au/products/1206421>



DIN rail perforated, acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>



NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/au/products/1206434>



DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/au/products/0801762>



DIN rail, unperforated, acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored, Pack of 10 (20 m)

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>



NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/au/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/au/products/1201730>



DIN rail perforated, similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>



NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/au/products/1201714>



DIN rail, unperforated, similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/au/products/0806602>



DIN rail perforated, similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white, Pack of 25 (50 m)

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>



NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/au/products/1204135>



DIN rail, unperforated, similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver, Pack of 10 (20 m)

NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/au/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>

NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/au/products/1206599>



DIN rail perforated, similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/au/products/1206586>



DIN rail, unperforated, similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>



NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/au/products/1201895>



DIN rail, unperforated, similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored, Pack of 10 (20 m)

NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/au/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>

NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/au/products/1201798>




DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver, Pack of 10 (20 m)

ZB 8:UNBEDRUCKT - Zack marker strip

1052002

<https://www.phoenixcontact.com/au/products/1052002>



Zack marker strip, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

URTK/S - Test disconnect terminal block




0311087

<https://www.phoenixcontact.com/au/products/0311087>

ZB 8 CUS - Zack marker strip

0825011

<https://www.phoenixcontact.com/au/products/0825011>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

UC-TM 8 - Marker for terminal blocks

0818072

<https://www.phoenixcontact.com/au/products/0818072>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 56

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>

UC-TM 8 CUS - Marker for terminal blocks

0824597

<https://www.phoenixcontact.com/au/products/0824597>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 56

UCT-TM 8 - Marker for terminal blocks

0828740

<https://www.phoenixcontact.com/au/products/0828740>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 42

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>



UCT-TM 8 CUS - Marker for terminal blocks

0829616

<https://www.phoenixcontact.com/au/products/0829616>




Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 8.2 mm, lettering field size: 7.6 x 10.5 mm, Number of individual labels: 42

ZB 8,LGS:FORTL.ZAHLEN - Zack marker strip

1052015

<https://www.phoenixcontact.com/au/products/1052015>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>

ZB 8,QR:FORTL.ZAHLEN - Zack marker strip

1052028

<https://www.phoenixcontact.com/au/products/1052028>




Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

ZB 8,LGS:L1-N,PE - Marker for terminal blocks

1052413

<https://www.phoenixcontact.com/au/products/1052413>



Marker for terminal blocks, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, horizontal: L1, L2, L3, N, PE, L1, L2, L3, N, PE, mounting type: snapped, for terminal block width: 8.2 mm, lettering field size: 10.5 x 8.15 mm, Number of individual labels: 10

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>

CLIPFIX 35 - End clamp

3022218

<https://www.phoenixcontact.com/au/products/3022218>



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray

CLIPFIX 35-5 - End clamp

3022276

<https://www.phoenixcontact.com/au/products/3022276>



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>




E/NS 35 N - End clamp

0800886

<https://www.phoenixcontact.com/au/products/0800886>

End clamp, width: 9.5 mm, color: gray



E/UK - End clamp

1201442

<https://www.phoenixcontact.com/au/products/1201442>

End clamp, material: PA, color: gray, Mounting on a DIN rail NS 32 or NS 35



URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>



E/UK 1 - End clamp

1201413

<https://www.phoenixcontact.com/au/products/1201413>



End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray

PSBJ 3,5/18/6 FARBLOS - Female test connector

0311391

<https://www.phoenixcontact.com/au/products/0311391>



Female test connector, number of positions: 1, color: transparent

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>



PSBJ 3,5/18/6 BK - Female test connector

0311388

<https://www.phoenixcontact.com/au/products/0311388>

Female test connector, number of positions: 1, color: black



PSBJ 3,5/18/6 GY - Female test connector

0311375

<https://www.phoenixcontact.com/au/products/0311375>

Female test connector, number of positions: 1, color: gray



URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>



PSBJ 3,5/18/6 VT - Female test connector

0311362

<https://www.phoenixcontact.com/au/products/0311362>



Female test connector, number of positions: 1, color: violet

PSBJ 3,5/18/6 GN - Female test connector

0311359

<https://www.phoenixcontact.com/au/products/0311359>



Female test connector, number of positions: 1, color: green

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>



PSBJ 3,5/18/6 YE - Female test connector

0311346

<https://www.phoenixcontact.com/au/products/0311346>



Female test connector, number of positions: 1, color: yellow

PSBJ 3,5/18/6 BU - Female test connector

0311333

<https://www.phoenixcontact.com/au/products/0311333>



Female test connector, number of positions: 1, color: blue

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>



PSBJ 3,5/18/6 RD - Female test connector

0311320

<https://www.phoenixcontact.com/au/products/0311320>

Female test connector, number of positions: 1, color: red



PSBJ 3,5/18/6 WH - Female test connector

0311317

<https://www.phoenixcontact.com/au/products/0311317>

Female test connector, number of positions: 1, color: white



URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>



PSBJ-URTK/S RD - Female test connector

0311744

<https://www.phoenixcontact.com/au/products/0311744>



Female test connector, number of positions: 1, color: red

PSBJ-URTK/S BU - Female test connector

0311757

<https://www.phoenixcontact.com/au/products/0311757>



Female test connector, number of positions: 1, color: blue

URTK/S - Test disconnect terminal block

0311087

<https://www.phoenixcontact.com/au/products/0311087>

PSBJ-URTK/S YE - Female test connector

0311731

<https://www.phoenixcontact.com/au/products/0311731>



Female test connector, number of positions: 1, color: yellow

PSBJ-URTK/S GN - Female test connector

0311760

<https://www.phoenixcontact.com/au/products/0311760>



Female test connector, number of positions: 1, color: green

URTK/S - Test disconnect terminal block



0311087

<https://www.phoenixcontact.com/au/products/0311087>

PSBJ-URTK/S VT - Female test connector

0311773

<https://www.phoenixcontact.com/au/products/0311773>

Female test connector, number of positions: 1, color: violet



PSBJ-URTK/S BK - Female test connector

0311728

<https://www.phoenixcontact.com/au/products/0311728>

Female test connector, number of positions: 1, color: black



Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT PTY Ltd
Unit 7, 2-8 South Street
Rydalmere NSW 2116
1300 786 411
customerservice@phoenixcontact.com.au