

https://www.phoenixcontact.com/au/products/3030242



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Plug-in bridge, pitch: 6.2 mm, number of positions: 3, color: red

Your advantages

• The 2- to 50-pos. jumpers can bridge up to 50 terminal blocks in the two bridge shafts of the CLIPLINE complete system in one step

Commercial Data

| Item number | 3030242 |
|--------------------------------------|--------------------|
| Packing unit | 50 pc |
| Minimum order quantity | 50 pc |
| Sales Key | BE2Z2X |
| Product Key | BE2Z2X |
| Catalog Page | Page 98 (C-1-2019) |
| GTIN | 4017918188566 |
| Weight per Piece (including packing) | 2.871 g |
| Weight per Piece (excluding packing) | 2.854 g |
| Customs tariff number | 85366990 |
| Country of origin | DE |



https://www.phoenixcontact.com/au/products/3030242



Technical Data

Product properties

| Product type | Jumper |
|---------------------|--------|
| Number of positions | 3 |
| Pitch | 6.2 mm |

Electrical properties

| Maximum load current | 32 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be |
|----------------------|--|
| | found in the accessories data for the respective modular terminal |
| | blocks.) |

Connection data

| Maximum load current | 32 A (The current values for the jumpers can deviate when used |
|----------------------|---|
| | in different modular terminal blocks. The precise values can be |
| | found in the accessories data for the respective modular terminal |
| | blocks.) |

Dimensions

| Width | 16.9 mm |
|--------|---------|
| Height | 23 mm |
| Pitch | 6.2 mm |

Material specifications

| Color | red |
|--|--------|
| Material | Copper |
| Flammability rating according to UL 94 | V0 |
| Insulating material | PA |

Mounting

| Mounting type Plug-in mounting |
|--------------------------------|
|--------------------------------|


3030242

https://www.phoenixcontact.com/au/products/3030242



Drawings

Schematic diagram



Please note a reduction of the nominal voltage if the FBS bridges are configured by breaking out contact tabs or cutting to a specific length



https://www.phoenixcontact.com/au/products/3030242



Classifications

ECLASS

| ECLASS-10.0.1 | 27141140 |
|---------------|----------|
| ECLASS-11.0 | 27141140 |
| ECLASS-12.0 | 27141140 |
| ECLASS-13.0 | 27250303 |
| | |

ETIM

| ETIM 8.0 | EC000489 |
|----------|----------|

UNSPSC

| UNSPSC 21.0 | 39121400 |
|-------------|----------|
|-------------|----------|

3030242

https://www.phoenixcontact.com/au/products/3030242



Environmental Product Compliance

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
| | No hazardous substances above threshold values |



https://www.phoenixcontact.com/au/products/3030242



Accessories

CUTFOX-FBS - Front cutter

1212124

https://www.phoenixcontact.com/au/products/1212124



Cutting tool, for separating individual jumper bars from FBS ... plug-in bridges and EB ... insertion bridges

FBSC - Protective cap

3012325

https://www.phoenixcontact.com/au/products/3012325



Covering hood, provides reliable shock protection when using cut-to-length FBS . ..-5 and FBS ...-6 bridges, color: red

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT PTY Ltd Unit 7, 2-8 South Street Rydalmere NSW 2116 1300 786 411 customerservice@phoenixcontact.com.au